Artificial neural networks and remote sensing for volumetric prediction in a

Eucalyptus sp. plantation

Redes neurais artificiais e sensoriamento remoto para predição volumétrica em um povoamento de *Eucalyptus* sp.

Redes neuronales artificiales y teledetección para la predicción volumétrica en plantaciones de

Eucalyptus sp.

Received: 09/10/2021 | Reviewed: 09/14/2021 | Accept: 09/17/2021 | Published: 09/19/2021

Alessandro Araujo Amaral de Almeida ORCID: https://orcid.org/0000-0002-0764-7558 Federal University of São Carlos, Brazil E-mail: aalmeidaalessandro@gmail.com Monica Fabiana Bento Moreira Thiersch ORCID: https://orcid.org/0000-0001-8039-0253 Federal University of São Carlos, Brazil E-mail: monicathiersch@ufscar.br Lucas Kröhling Bernardi ORCID: https://orcid.org/0000-0002-7199-989X Federal University of São Carlos, Brazil E-mail: bernardilucas@estudante.ufscar.br Franciane Andrade de Pádua ORCID: https://orcid.org/0000-0002-3349-8648 Federal University of São Carlos, Brazil E-mail: franciane@ufscar.br Argemiro José Moreno Arteaga ORCID: https://orcid.org/0000-0002-4700-3263 Federal University of Campina Grande, Brazil E-mail: argemor29@hotmail.com **Claudio Roberto Thiersch** ORCID: https://orcid.org/0000-0003-1558-3168 Federal University of São Carlos, Brazil E-mail: crthiersch@ufscar.br

Abstract

Forest inventory is an important tool for estimating the production of forest stands and normally employs traditional methods for volume estimation. However, as a result of technological advancements, artificial neural networks and remote sensing have assumed a prominent role in the forestry sector since satellite images have different components that correlate with the dendrometric variables and can be used as auxiliary variables. The objective of this work was to evaluate the performance of artificial neural networks regarding the estimation of volume in a Eucalyptus sp. plantation with the use of satellite images. Pre-cut inventory data were used with ages varying between 5.3 and 6.3 years. The variables used were volume, age, 4 bands of the satellite image with a 10 m spatial resolution from Sentinell-2 satellite, ratio between the bands, NDVI, and genetic material. All processing was performed using the free software R. The evaluation criteria for the neural network were percentage of residual standard error and graphical analysis of the residues. The best neural network configuration for volume estimation presented a residual standard error of 10.63% and 12.00% for training and validation, respectively. The methodology proposed in this work proved to be efficient in estimating the volume of the stand.

Keywords: Forest inventory; Machine learning; Artificial neural network; Eucalyptus sp. plantation.

Resumo

O Inventário Florestal é uma ferramenta importante para estimar a produção de povoamentos e, normalmente, emprega métodos tradicionais para a estimativa de volume. Entretanto, como resultado dos avanços tecnológicos, as redes neurais artificiais e o sensoriamento remoto surgem cada vez mais no setor florestal, visto que as imagens de satélite têm diferentes componentes que correlacionam-se com variáveis dendrométricas e podem ser usadas como variáveis auxiliares. O objetivo deste trabalho foi avaliar a performance de redes neurais artificiais em estimar o volume de um povoamento de Eucalyptus sp. com o uso de imagens de satélite. Dados de inventário pré-corte foram utilizados, com idades variando entre 5,3 e 6,3 anos. As variáveis usadas foram: volume, idade, 4 bandas da imagem de satélite com resolução espacial de 10 m proveniente do satélite Sentinell-2, razão entre as bandas, NDVI e material

genético. Todo o processamento dos dados foi realizado utilizando o software livre R. Os critérios de avaliação da rede neural foram o erro padrão residual em porcentagem e as análises gráficas dos resíduos. A melhor configuração de rede neural para estimativa de volume apresentou erro padrão residual de 10,63% e 12,00% para treinamento e validação, respectivamente. A metodologia proposta neste trabalho provou-se eficiente em estimar o volume do povoamento.

Palavras-chave: Inventário florestal; Aprendizado de máquina; Redes neurais artificiais; Povoamento de *Eucalyptus* sp.

Resumen

El inventario forestal es una herramienta importante para estimar la producción de la masa de una plantación forestal, que normalmente, es determinada empleando métodos tradicionales. Sin embargo, como resultado de los avances tecnológicos, las redes neurales artificiales y la teledetección han asumido un papel destacado en el sector forestal, ya que las imágenes de satélite tienen diferentes componentes que se correlacionan con las variables dendrométricas y pueden ser utilizadas como variables auxiliares. El objetivo de este trabajo fue evaluar el rendimiento de las redes neuronales artificiales en la estimación del volumen en una plantación de Eucalyptus sp. con el uso de imágenes de satélite. Se utilizaron datos inventariados de precorte, con edades que varían entre 5,3 y 6,3 años. Las variables utilizadas fueron volumen, edad, 4 bandas de imagen digital registrada por el satélite Sentinell-2 con resolución espacial de 10 m, relación entre las bandas, NDVI y material genético. Todo el procesamiento fue realizado con el software R de libre acceso. Los criterios de evaluación de las redes neuronales fueron el porcentaje de error estándar residual y el análisis gráfico de los residuos. La mejor configuración de red neuronal resultante para la estimación del volumen presentó un error estándar residual del 10,63% y del 12,00% para el entrenamiento y la validación, respectivamente. La metodología propuesta en este trabajo demostró ser eficiente en la estimación del volumen de la plantación.

Palabras clave: Inventario forestal; Aprendizaje de máquina; Redes neuronales artificiales; Plantación de *Eucalyptus* sp.

1. Introduction

In the last two decades, the majority of research conducted within the scope of satellite images together with Artificial Neural Network (ANN) has been focused on the estimation of biomass in forest stands, being estimated in units of mass (Frazier et al., 2014; López-Serrano et al., 2016; Lu et al., 2016; Sarker & Nichol, 2011; Wang et al., 2011). Although biomass can be used to obtain the wood volume with bark using allometric equations, this has not been the aim of most of the research developed.

Coulibaly et al. (2008) mapped the biomass of a Canadian forest using ANN and Kriging interpolation, with geospatial data and various vegetation indexes extracted from the Ikonos satellite image. Wang & Xing (2008) and Zhu et al. (2015) applied ANN to model the biomass using spectral bands and vegetation indices from Landsat 5 and Worldview-2 satellites, in Chinese forests. Using SAR data, Del Frate & Solimini (2004) were able to calculate biomass in forests located in France, French Guiana and the Netherlands; similarly, Santi et al. (2015, 2017) estimated biomass in measures of volume and weight in the San Rossore e Molise park in Italy. In India, Nandy et al. (2017) in the Barkot forest and Deb et al. (2017) in the Bundelkhand region, measured forest biomass using ANN, integrating field inventory data, spectral bands, texture and vegetation indexes from the Resourcesat 1 and 2 satellite images. Almeida et al. (2009) carried out a study in an area located in the Amazon Rainforest, estimating the forest biomass processing ANN with spectral bands and vegetation indexes, in the first case, and bands and textures, in the second case, as input variables. Ferraz et al. (2014) performed a study in a Tropical Rainforest fragment, processing ANN with spectral bands and vegetation indexes stellite.

In addition to all the aforementioned investigations, several studies have been carried out worldwide in different types of forest stands using ANN to estimate the volume of biomass and other morphological parameters of the trees, mainly using data obtained from field work and disregarding information from remote sensing (Bhering et al., 2015; Gorgens et al., 2009; Ingram et al., 2005; Jutras et al., 2009; Martins et al., 2016; Silva et al., 2009; Tavares Júnior et al., 2019; Vahedi, 2016).

From what has been observed, there are only a few studies on estimating stand volume or stand parameters using ANN and remote sensing data such as from Landsat, SPOT and SAR images (dos Reis et al., 2018; Miguel et al., 2015; Moreno et al., 2019; Sakici & Günlü, 2018; Santi et al., 2015; Zhou et al., 2020).

Zhou et al. (2020) applied ANN to determine the volume of pine wood in a forest area in China, with images from the SPOT satellite. Miguel et al. (2015) evaluated the effectiveness of ANN in predicting the volume of wood in tree vegetation in a Brazilian Savanna area from spectral bands and vegetation indexes using images from the Resourcesat-1 satellite. Similarly, Moreno et al. (2019) quantified the wood volume from *Eucalyptus* sp. with satellite images obtained from SPOT 6. Additionally, no studies have been found using exact procedures for thematic mapping of the volume of wood or biomass in forest stands using data derived from Sentinel-2 satellite images through the structuring of ANN, so there is a need for the development of research with this approach to identify its potential application.

This study aims to evaluate the efficiency of an artificial neural network methodology, associated with Sentinel-2 satellite images, in estimating the volume (including bark) of a *Eucalyptus* sp. stand.

2. Methodology

The data used came from 569 rectangular permanent plots with an average area of 280.38 m^2 each of a *Eucalyptus* sp. plantation composed of nine different clonal varieties, with 3x2 m spacing between plants, and ages ranging from 5.3 to 6.3 years. In each plot, circumference at breast height (1.3 m above ground) of all trees, the total height of the first five trees, and dominant tree height were measured, according to Assman (1970).

The plantation was located in the interior of the state of São Paulo, in the city of Botucatu, Brazil (Figure 1). According to the Köeppen climate classification, the local climate is hot temperate (mesothermal).



Figure 1. Location of *Eucalyptus* sp. plantations in a satellite image of the city of Botucatu.

Source: Authors (2021).

The multispectral data used to conduct the work consisted of Sentinel-2 satellite images. The images were chosen following the criterion of compatibility between date of image and date of execution of the inventory, in order to minimize the

temporal variations in the forest typologies. Both forest inventory and images were from 2016. Sentinel-2 satellite has a spatial resolution of 10 m, 20 m and 30 m and a 13-band spectral resolution. The proposed work used a 10 m spatial resolution and a 4-band spectral resolution (B02, 490 nm central wavelength, blue; B03, 560 nm central wavelength, green; B04, 665 nm central wavelength, red; and B08, 842 nm central wavelength, near infrared).

The projection adopted was UTM 22 S - Universal Transverse Mercator - and the DATUM SIRGAS 2000 - Geocentric Reference System for the Americas.

Image information and vegetation indexes were obtained through the statistical software R (R Core Team, 2017), with the aid of the rgdal (Bivand et al., 2017) and raster (Hijmans, 2016) packages. In addition, all processing of the neural networks, tuning and network application were performed in software R.

Images were cut according to farm plots (area of interest), and only included information on the areas of effective planting in the image archive. Based on this, a raster was generated containing the information of each pixel, i.e., its coordinates (x, y) and the respective gray levels of each of the four spectral bands. The normalized difference vegetation index (NDVI) was calculated, as well as the simple ratio between the bands, i.e., band 2 divided by band 3, band 2 divided by band 4, and so on. By doing this, it is possible to discriminate subtle differences in the spectral behavior of different targets, whereas only gross differences are observed in original bands (Araujo & Mello, 2010).

Regarding the networks, training was carried out to obtain networks for estimating volume including bark. The volume, age, bands (Blue, Green, Red and near Infrared), ratio between bands and NDVI were used as input numerical variables. The genetic material was used as a categorical variable, represented by a sequence from 1 to 9.

Volumes were obtained using Smalian's formula and ranged from 144 to 456 m³/ha. Such variation might be due to damage (wind, burning, among others) in parts of the plantation. Information on the bands was extracted from raster using a 100 m buffer around the coordinates of each plot and the NDVI obtained by the mathematical equation NDVI = (ivp - vm) / (ivp + vm); where: ivp was the reflectance in the near infrared region and vm was the reflectance in the red region.

To obtain the estimate of the volume with bark, the data were randomly divided into two parts: 70% towards training of the networks and 30% towards generalization, i.e., applying the trained networks to the data not used in the training for validation. After selecting the data for the training of the neural networks, data normalization was performed. This step consists in the transformation of each numerical variable into values between 0 and 1. Normalization is a technique used to transform variables and homogenize them, thus preventing very high-value variables from interfering with the estimates (Gorgens et al., 2009).

Network learning was supervised, i.e., the networks received two sets of values: an input set and an output set (Haykin, 2001b). Thus, training consisted in an optimization of the network parameters, so that they could respond to the inputs as expected until the standard errors of the output, generated by the network, reached the desired minimum value (Leal et al., 2015).

The present study used a Multi-Layer Perceptron architecture with 21 neurons in the input layer, 2 intermediate hidden layers and 1 neuron in the output layer (Figure 2). This was the only ANN architecture used because, according to Chiarello et al. (2019), in forest biometrics and modeling state of the art, regarding the use of artificial neural networks, 78% of works used Multi-layer Perceptron architecture when the second most used was Radial Basis Function network with only 12% of adoption.



Figure 2. Flowchart explaining the methodology used in the work.

The algorithm adopted was Backpropagation, which iteratively seeks to find the minimum difference between the desired outputs and the outputs obtained by the neural network with minimal error. The weights between the layers were adjusted through backpropagation of the error found in each iteration (Haykin, 2001a).

In the study were evaluated 25 different configurations of neural networks referring to the number of variables in the hidden layers. A reduction factor was applied so that the number of variables of the first hidden layer was reduced by half in relation to the number of input variables and, similarly, a reduction factor was applied to the second hidden layer in order to limit a maximum number of variables based on the number of variables of the first hidden layer.

The evaluations of the estimates by the artificial neural network in the training and validation stages were conducted according to residual standard error in cubic meters per hectare and in percentage (Sxy). The closer to zero, the higher the accuracy of the estimates and graphical analysis of the errors (m³). Error analysis was carried out based on a residual distribution and quantile-quantile graph, which was used to verify if the frequency distribution of the data fit a normal distribution.

3. Results and Discussion

Regarding the bands (Table 1), the means obtained show the difference between the average values of gray level that correspond to the brightness of the image (Ribeiro et al., 2009). By observing each band's standard deviation, it is possible to verify that every band presents a contrast of the image. In the present work, B08 was the band with the greatest standard deviation, which resulted in the greatest contrast of the image among the bands, i.e., it showed the clearest image, with the greatest scattering of gray levels. Conversely, when a band has a low standard deviation and low contrast, it will have darker images.

The normalized difference vegetation index normalizes the simple ratio to the range of -1 to 1. Areas with intense vegetation approach the upper levels and wetlands approach the lower limit (Cordeiro et al., 2017). Table 1 shows that the average NDVI of the data is close to 1 indicating that the area generally presents intense vegetation, not showing planting faults or areas without vegetation.

Variable	Minimum	Average	Maximum	Standard Deviation
Volume (m ³ /ha)	143.89	315.45	456.29	± 46.79
age (years)	5.30	5.69	6.30	± 0.32
B02	758	779	815	± 9.71
B03	581	621	675	± 16.61
B04	363	406	510	± 21.52
B08	2220	2734	3421	± 266.79
NDVI	0.68	0.74	0.80	± 0.02

Table 1. Descriptive analysis of numerical variables. (B02): 490 nm central wavelength, blue; (B03): 560 nm central wavelength, green; (B04): 665 nm central wavelength, red; (B08): 842 nm central wavelength, near infrared; (NDVI): normalized difference vegetation index.

Source: Authors (2021).

Figure 3 shows the configuration of the neural network that was selected as being the best among the trained ones. Its architecture consists of 8 neurons in the first hidden layer, 3 neurons in the second hidden layer and 1 neuron in the output layer (8-3-1), the latter being the variable of interest for the calculation of the volume.



Figure 3. Architecture of the trained neural network, including synaptic weights.

Source: Authors (2021).

The first layer (1) is the input and presents the variables used, such as NDVI and age in years, and where: b2, b3, b4, and b8 are the bands; b2_b3, b2_b4, b2_b8, b3_b4, b3_b8, and b4_b8 are the ratio between the bands; matgen1 to matgen9 are the genetic materials. The second (2) and third (3) layers are the hidden layers, and the last layer (4) is the output layer, i.e., the variable of interest (volume). The layers show the weights related to each neuron, which were updated at each iteration of the network so that the final result was the smallest possible error between the desired value and the observed value.

Table 2 shows the neural network that obtained the best Sxy (%) and the best distribution of residuals among the analyzed architectures. As can be noted, the values of residual standard error in percentage for training and for validation were 10.63% (38.33 m³/ha), and 12.00% (33.35 m³/ha), respectively. Lima et al. (2017) evaluated the neural networks efficiency in

growth and production modelling at total stand level of *Eucalyptus* sp. clones and obtained 2-7-1 as best architecture with standard error of 8.48% and 12.90% for training and validation, respectively. On the other hand, Miguel et al. (2015) obtained a standard error of estimate (Syx) of 4.93% for training and 6.01% for validation, when evaluating the performance of the neural networks for modeling the volume of wood with data from ResourceSat1 satellite.

 Table 2. Characteristics and performance of the selected neural network. (ANN): Artificial Neural Network; (MLP):

 Multilayer Perceptron; (Syx): Standard error of estimate (m³ or %).

ANN	Туре	Architecture	Training		Generalization	
			Syx (m ³ /ha)	Syx (%)	Syx(m ³ /ha)	Syx(%)
12	MLP	8-3-1	33.35	10.63	38.33	12.00

Source: Authors (2021).

Sakici and Günlü (2018) found that when estimating some stand attributes (i.e. mean diameter, basal area, stand volume and number of trees) of Crimean pine stands using texture values obtained from satellite images, in that case from Landsat 8 OLI, some ANN models performed better than multiple linear regression models. The R² values obtained for the best ANN models increased between 48% and 239% for the stand parameters compared to the regression models, being the ANN models more accurate for mixed, broadleaf and conifer forest types than linear regression model.

Zhou et al. (2020), estimated the stock volume of pine plantations in China, processing spectral bands and image texture from SPOT satellite with ANN, obtaining Syx values of 31.45% (45.44 m³/ha). Also in Italy, Santi et al. (2015), with L and C bands of SAR images, applied ANN to determine the volume of wood in forests with pine and other oak forests, reaching Syx (m³/ha) results of 40 m³/ha and 30 m³/ha, correspondingly.

Thus, by comparing the results obtained in the present work with the results from other authors, it can be said that the database studied here obtained satisfactory results. According to Oliveira (2012), better results can be achieved by analyzing the existing correlations between the information extracted from the images and the dendrometric data, as well as evaluating new combinations in relation to the activation functions, and selecting the input variables that influence the output variable (volume) in the neural networks by applying the stepwise method.

The fact that the error of the validation is close to that of the training indicates the non-occurrence of overfitting, i.e., the variables used for the training were sufficient for the neural network to be generalized and applied to other data. In addition, it can be noted that different configurations of the neural networks in terms of algorithm, number of hidden layers, activation function, input variables, among others, influence the final results obtained by the neural networks. Figure 4 shows a map with the values of the estimated volumes found by neural networks in a *Eucalyptus* sp. plantation. Volumes range from 228.40 to 366.50 m³/ha.

Although the statistics presented are good indicators of the results obtained, it is fundamental to conduct a graphical analysis of the residues, since tendentious errors may occur and not be detected by the statistics. This would lead to underestimation, in case the estimated value was lower than that observed, or overestimation, otherwise. Figure 5 shows the dispersion of the residues with respect to the observed values and the quantile-quantile plot.



Figure 4. Volume estimates found by the neural networks.

Source: Authors (2021).

Figure 5. Scatter plot of residues (a) and quantile-quantile (b) (q-q). The black line in plot (a) represents lowess regression.





When analyzing Figure 5 (a), where the waste distributions of the estimated volumes for the analyzed database are presented, it is verified that the neural networks tend to overestimate when the volume is less than approximately 330 m³/ha and to underestimate when the volume exceeds approximately 330 m³/ha, as can be observed in the trend line. Looking at Figure 5 (b), in turn, one may interpret that the residuals tend to a normal distribution because the points are close to a line, and the closer to a line, the closer the residuals are to the normal distribution.

The results presented and analysis conducted show that the results were efficient for the proposed problem. Likewise, Silva et al. (2009) evaluated the performance of the neural networks in estimating the volume of eucalyptus wood and concluded that the networks were suitable to the tested situations and, therefore, recommend their use for volume estimates. However, dos Reis et al. (2018), when studying spatial prediction of basal area and volume in Eucalyptus stands using Landsat TM data, found that ANN, in general, are very sensitive to the variation of input parameters, more than other methods, especially when using a restricted dataset, resulting in estimates that were not compatible with the forest inventory estimates. Dos Reis et al. (2018) also pointed out that their results need to be interpreted cautiously, as they are limited to a homogenous and relatively small study area, but it still showcases the importance of using remote sensing data and prediction methods for

volume estimation. These statements reinforce the idea that further studies are needed with the use of artificial neural networks to estimate forest parameters in order to find reliable methodologies with more consistent results.

4. Conclusion

The ANN technique together with the use of images from Sentinel-2 satellite made it possible to estimate the volume of *Eucalyptus* sp. plantations with statistically acceptable error values, 10.63% for training and 12.00% for validation.

The network that presented the best estimates in this work has an architecture with 8 and 3 neurons in the first layer and second hidden layers, respectively, and is composed of 21 input variables.

This methodology can be applied to other inventories with no additional costs since all processing was carried out using the free software R and satellite images obtained free of charge.

New studies are encouraged, especially those using free image sources such as LANDSAT, MODIS, ASTER, and Sentinel, for example. Regarding Forest Inventories, companies are always trying to reduce costs, and free satellite images are great alternatives when used together with artificial neural networks to ensure precision with no additional cost.

Acknowledgments

This study was financed in part by the Coordenação de Aperfeiçoamento de Pessoal de Nível Superior - Brazil (CAPES) - Finance Code 001.

References

Almeida, A. da C., Barros, P. L. C., Monteiro, J. H. A., & Rocha, B. R. P. (2009). Estimation of Aboveground Forest Biomass in Amazonia with Neural Networks and Remote Sensing. *IEEE Latin America Transactions*, 7(1), 27–32. https://doi.org/10.1109/TLA.2009.5173462

Araujo, T. P., & Mello, F. M. (2010). Processamento de imagens digitais - Razão entre bandas. Geociencias, 29(1), 121-131.

Assman, E. (1970). The principles of forest yield study (P. W. Davis (ed.); 1st ed.). Pergamon Press.

Bhering, L. L., Cruz, C. D., Peixoto, L. de A., Rosado, A. M., Laviola, B. G., & Nascimento, M. (2015). Application of neural networks to predict volume in eucalyptus. *Crop Breeding and Applied Biotechnology*, *15*(3), 125–131. https://doi.org/10.1590/1984-70332015v15n3a23

Bivand, R., Keitt, T., & Rowlingson, B. (2017). rgdal: Bindings for the Geospatial Data Abstraction Library. [S.1.], 2017. R package version 1.2-8. https://CRAN.R-project.org/package=rgdal

Chiarello, F., Steiner, M. T. A., Oliveira, E. B. DE, Arce, J. E., & Ferreira, J. C. (2019). Artificial neural networks applied in forest biometrics and modeling: state of the art (january/2007 to july/2018). *cerne*, 25(2), 140–155. https://doi.org/10.1590/01047760201925022626

Cordeiro, A. P. A., Berlato, M. A., Fontana, D. C., Melo, R. W. de, Shimabukuro, Y. E., & Fior, C. S. (2017). Regiões homogêneas de vegetação utilizando a variabilidade do ndvi. *Ciência Florestal*, 27(3), 883. https://doi.org/10.5902/1980509828638

Coulibaly, L., Migolet, P., Adegbidi, H. G., Fournier, R., & Hervet, E. (2008). Mapping Aboveground Forest Biomass from Ikonos Satellite Image and Multi-Source Geospatial Data using Neural Networks and a Kriging Interpolation. *IGARSS 2008 - 2008 IEEE International Geoscience and Remote Sensing Symposium*, III-298-III–301. https://doi.org/10.1109/IGARSS.2008.4779342

Cutler, M. E. J., Boyd, D. S., Foody, G. M., & Vetrivel, A. (2012). Estimating tropical forest biomass with a combination of SAR image texture and Landsat TM data: An assessment of predictions between regions. *ISPRS Journal of Photogrammetry and Remote Sensing*, 70, 66–77. https://doi.org/10.1016/j.isprsjprs.2012.03.011

Deb, D., Singh, J. P., Deb, S., Datta, D., Ghosh, A., & Chaurasia, R. S. (2017). An alternative approach for estimating above ground biomass using Resourcesat-2 satellite data and artificial neural network in Bundelkhand region of India. *Environmental Monitoring and Assessment*, 189(11), 576. https://doi.org/10.1007/s10661-017-6307-6

Del Frate, F., & Solimini, D. (2004). On Neural Network Algorithms for Retrieving Forest Biomass From SAR Data. *IEEE Transactions on Geoscience and Remote Sensing*, 42(1), 24–34. https://doi.org/10.1109/TGRS.2003.817220

Reis, A. A., Carvalho, M. C., de Mello, J. M., Gomide, L. R., Ferraz Filho, A. C., & Acerbi Junior, F. W. (2018). Spatial prediction of basal area and volume in Eucalyptus stands using Landsat TM data: an assessment of prediction methods. *New Zealand Journal of Forestry Science*, 48(1), 1. https://doi.org/10.1186/s40490-017-0108-0

Ferraz, A. S., Soares, V. P., Soares, C. P. B., Ribeiro, C. A. A. S., Binoti, D. H. B., & Leite, H. G. (2014). Estimativa do estoque de biomassa em um fragmento florestal usando imagens orbitais. *Floresta e Ambiente*, 21(3), 286–296. https://doi.org/10.1590/2179-8087.052213

Foody, G. M., Cutler, M. E., McMorrow, J., Pelz, D., Tangki, H., Boyd, D. S., & Douglas, I. (2001). Mapping the biomass of Bornean tropical rain forest from remotely sensed data. *Global Ecology and Biogeography*, *10*(4), 379–387. https://doi.org/10.1046/j.1466-822X.2001.00248.x

Frazier, R. J., Coops, N. C., Wulder, M. A., & Kennedy, R. (2014). Characterization of aboveground biomass in an unmanaged boreal forest using Landsat temporal segmentation metrics. *ISPRS Journal of Photogrammetry and Remote Sensing*, *92*, 137–146. https://doi.org/10.1016/j.isprsjprs.2014.03.003

Gorgens, E. B., Leite, H. G., Santos, H. do N., & Gleriani, J. M. (2009). Estimação do volume de árvores utilizando redes neurais artificiais. *Revista Árvore*, 33(6), 1141–1147. https://doi.org/10.1590/S0100-67622009000600016

Haykin, S. (2001a). Perceptrons de múltiplas camadas. In Redes Neurais: princípios e prática (2nd ed., pp. 182-198). Bookman.

Haykin, S. (2001b). Processos de Aprendizagem. In Redes Neurais: princípios e prática (2nd ed., pp. 75–91). Bookman.

Hijmans, R. J. (2016). raster: Geographic Data Analysis and Modeling. R package version 2.5-8. Retrieved from: https://CRAN.R-project.org/package=raster

Ingram, J. C., Dawson, T. P., & Whittaker, R. J. (2005). Mapping tropical forest structure in southeastern Madagascar using remote sensing and artificial neural networks. *Remote Sensing of Environment*, 94(4), 491–507. https://doi.org/10.1016/j.rse.2004.12.001

Jutras, P., Prasher, S. O., & Mehuys, G. R. (2009). Prediction of street tree morphological parameters using artificial neural networks. *Computers and Electronics in Agriculture*, 67(1–2), 9–17. https://doi.org/10.1016/j.compag.2009.02.008

Leal, A. J. F., Miguel, E. P., Baio, F. H. R., Neves, D. de C., & Leal, U. A. S. (2015). Redes neurais artificiais na predição da produtividade de milho e definição de sítios de manejo diferenciado por meio de atributos do solo. *Bragantia*, 74(4), 436–444. https://doi.org/10.1590/1678-4499.0140

Lima, M. B. de O., Lustosa-Junior, I. M., Oliveira, E. M., Ferreira, J. C. B., Soares, K. L., & Miguel, E. P. (2017). Artificial neural networks in whole-stand level modeling of Eucalyptus plants. African Journal of Agricultural Research, 12(7), 524–534. https://doi.org/10.5897/AJAR2016.12068

López-Serrano, P. M., López-Sánchez, C. A., Álvarez-González, J. G., & García-Gutiérrez, J. (2016). A Comparison of Machine Learning Techniques Applied to Landsat-5 TM Spectral Data for Biomass Estimation. *Canadian Journal of Remote Sensing*, 42(6), 690–705. https://doi.org/10.1080/07038992.2016.1217485

Lu, D., Chen, Q., Wang, G., Liu, L., Li, G., & Moran, E. (2016). A survey of remote sensing-based aboveground biomass estimation methods in forest ecosystems. *International Journal of Digital Earth*, 9(1), 63–105. https://doi.org/10.1080/17538947.2014.990526

Martins, E. R., Binoti, M. L. M. S., Leite, H. G., Binoti, D. H. B., & Dutra, G. C. (2016). Configuração de redes neurais artificiais para estimação da altura total de árvores de eucalipto. *Revista Brasileira de Ciências Agrárias - Brazilian Journal of Agricultural Sciences*, 11(2), 117–123. https://doi.org/10.5039/agraria.v11i2a5373

Miguel, E. P., Rezende, A. V., Leal, F. A., Matricardi, E. A. T., Vale, A. T. do, & Pereira, R. S. (2015). Redes neurais artificiais para a modelagem do volume de madeira e biomassa do cerradão com dados de satélite. *Pesquisa Agropecuária Brasileira*, 50(9), 829–839. https://doi.org/10.1590/S0100-204X2015000900012

Moreno Arteaga, A. J., Thiersch, M. F. B. M., Valente, R. O. A., Bernardi, L. K., Vasconcelos, S. L., & Thiersch, C. R. (2019). Espacialidad volumétrica de madera en plantaciones forestales usando redes neurales artificiales con imágenes de satélite. *Acta Agronómica*, 68(2), 142–150. https://doi.org/10.15446/acag.v68n2.78945

Nandy, S., Singh, R., Ghosh, S., Watham, T., Kushwaha, S. P. S., Kumar, A. S., & Dadhwal, V. K. (2017). Neural network-based modelling for forest biomass assessment. *Carbon Management*, 8(4), 305–317. https://doi.org/10.1080/17583004.2017.1357402

Oliveira, F. S. (2012). Uso de imagens do satélite ALOS para estimativa de parâmetros dendrométricos de plantios de eucalipto. Federal University of Viçosa, Viçosa, MG, Brazil.

R Core Team, 2017. R: A Language and Environment for Statistical Computing. Vienna, Austria. Retrieved from: https://www.R-project.org/

Ribeiro, B. M. G., Saito, E. A., Korting, T. S., Maeda, E. E., & Formaggio, A. R. (2009). Estudo da variância em imagens MODIS para diferentes classes de coberturas dos solos: estudo de caso em Querência – MT. In: Proceedings of the "2009 XIV Brazilian Symposium on Remote Sensing", 25-30 April 2009, INPE, Natal, RN, Brazil, pp. 1005-1012.

Sakici, O. E., & Günlü, A. (2018). Artificial Intelligence applications for predicting some stand attributes using landsat 8 OLI satellite data: a case study from Turkey. *Applied Ecology and Environmental Research*, *16*(4), 5269–5285. https://doi.org/10.15666/aeer/1604_52695285

Santi, E., Paloscia, S., Pettinato, S., Chirici, G., Mura, M., & Maselli, F. (2015). Application of Neural Networks for the retrieval of forest woody volume from SAR multifrequency data at L and C bands. *European Journal of Remote Sensing*, *48*(1), 673–687. https://doi.org/10.5721/EuJRS20154837

Santi, E., Paloscia, S., Pettinato, S., Fontanelli, G., Mura, M., Zolli, C., Maselli, F., Chiesi, M., Bottai, L., & Chirici, G. (2017). The potential of multifrequency SAR images for estimating forest biomass in Mediterranean areas. *Remote Sensing of Environment*, 200, 63–73. https://doi.org/10.1016/j.rse.2017.07.038

Sarker, L. R., & Nichol, J. E. (2011). Improved forest biomass estimates using ALOS AVNIR-2 texture indices. *Remote Sensing of Environment*, 115(4), 968–977. https://doi.org/10.1016/j.rse.2010.11.010

Silva, M. L. M. da, Binoti, D. H. B., Gleriani, J. M., & Leite, H. G. (2009). Ajuste do modelo de Schumacher e Hall e aplicação de redes neurais artificiais para estimar volume de árvores de eucalipto. *Revista Árvore*, *33*(6), 1133–1139. https://doi.org/10.1590/S0100-67622009000600015

Tavares Júnior, I., Rocha, J., Ebling, Â., Chaves, A., Zanuncio, J., Farias, A., & Leite, H. (2019). Artificial Neural Networks and Linear Regression Reduce Sample Intensity to Predict the Commercial Volume of Eucalyptus Clones. *Forests*, *10*(3), 268. https://doi.org/10.3390/f10030268

Vahedi, A. A. (2016). Artificial neural network application in comparison with modeling allometric equations for predicting above-ground biomass in the Hyrcanian mixed-beech forests of Iran. *Biomass and Bioenergy*, 88, 66–76. https://doi.org/10.1016/j.biombioe.2016.03.020

Wang, G., Zhang, M., Gertner, G. Z., Oyana, T., McRoberts, R. E., & Ge, H. (2011). Uncertainties of mapping aboveground forest carbon due to plot locations using national forest inventory plot and remotely sensed data. *Scandinavian Journal of Forest Research*, 26(4), 360–373. https://doi.org/10.1080/02827581.2011.564204

Wang, L. H., & Xing, Y. Q. (2008). Remote sensing estimation of natural forest biomass based on an artificial neural network. Ying yong sheng tai xue bao = The journal of applied ecology 19: 261–66.

Zhou, J., Zhou, Z., Zhao, Q., Han, Z., Wang, P., Xu, J., & Dian, Y. (2020). Evaluation of Different Algorithms for Estimating the Growing Stock Volume of Pinus massoniana Plantations Using Spectral and Spatial Information from a SPOT6 Image. *Forests*, *11*(5), 540. https://doi.org/10.3390/f11050540

Zhu, Y., Liu, K., Liu, L., Wang, S., & Liu, H. (2015). Retrieval of Mangrove Aboveground Biomass at the Individual Species Level with WorldView-2 Images. *Remote Sensing*, 7(9), 12192–12214. https://doi.org/10.3390/rs70912192